

**CARBON AND HIGH STRENGTH LOW ALLOY PLATE:
Permissible Variations in Width and Length for Sheared Plates,
1-1/2" and Under in Thickness; Length Only on
Universal Mill Plates 2-1/2" and Under in Thickness.**

Specified Dimensions, in Inches		Variations over Specified Width and Length ^a for Thickness, in., and Equivalent Weights, lb/ft ² , Given							
Length	Width	To 3/8, excl. To 15.3, excl.		3/8 to 5/8, excl. 15.3 to 25.5, excl.		5/8 to 1, excl. 25.5 to 40.8, excl.		1 to 2, excl. 40.8 to 81.7, excl.	
		Width	Length	Width	Length	Width	Length	Width	Length
To 120, excl.	To 60, excl.	3/8	1/2	7/16	5/8	1/2	3/4	5/8	1
	60 to 84, excl.	7/16	5/8	1/2	11/16	5/8	7/8	3/4	1
	84 to 108, excl.	1/2	3/4	5/8	7/8	3/4	1	1	1-1/8
	108 and Over.	5/8	7/8	3/4	1	7/8	1-1/8	1-1/8	1-1/4
120 to 240, excl.	To 60, excl.	3/8	3/4	1/2	7/8	5/8	1	3/4	1-1/8
	60 to 84, excl.	1/2	3/4	5/8	7/8	3/4	1	7/8	1-1/4
	84 to 108, excl.	9/16	7/8	11/16	15/16	13/16	1-1/8	1	1-3/8
	108 and Over.	5/8	1	3/4	1-1/8	7/8	1-1/4	1-1/8	1-3/8
240 to 360, excl.	To 60, excl.	3/8	1	1/2	1-1/8	5/8	1-1/4	3/4	1-1/2
	60 to 84, excl.	1/2	1	5/8	1-1/8	3/4	1-1/4	7/8	1-1/2
	84 to 108, excl.	9/16	1	11/16	1-1/8	7/8	1-3/8	1	1-1/2
	108 and Over.	11/16	1-1/8	7/8	1-1/4	1	1-3/8	1-1/4	1-3/4
360 to 480, excl.	To 60, excl.	7/16	1-1/8	1/2	1-1/4	5/8	1-3/8	3/4	1-5/8
	60 to 84, excl.	1/2	1-1/4	5/8	1-3/8	3/4	1-1/2	7/8	1-5/8
	84 to 108, excl.	9/16	1-1/4	3/4	1-3/8	7/8	1-1/2	1	1-7/8
	108 and Over.	3/4	1-3/8	7/8	1-1/2	1	1-5/8	1-1/4	1-7/8

^aPermissible variation under specified width and length, 1/4".

**Permissible Variations in Width for Mill Edge Carbon and High Strength
Low Alloy Plates Produced on Strip Mills.
(Applies to either Plates Produced from Coils or Plates Produced
in Discrete Cut Lengths of Flat Product).**

Specified Width, In.	Variations over Specified Width, In. ^c
To 14, excl	7/16
14 to 17, excl.	1/2
17 to 19, excl.	9/16
19 to 21, excl.	5/8
21 to 24, excl.	11/16
24 to 26, excl.	13/16
26 to 28, excl.	15/16
28 to 35, excl.	1-1/8
35 to 50, excl.	1-1/4
50 to 60, excl.	1-1/2
60 to 65, excl.	1-5/8
65 to 70, excl,	1-3/4
70 to 80, excl.	1-7/8
80 and Over	2

^cNo permissible variation under specified width.